Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Delo Starplex Moly 3% EP 2

Synonyms Delo Starplex Moly 3% EP 2 Product Code 510864

Recommended use: Grease

Supplier: Street Address: Web address:	Z Energy Limited 3 Queen's Wharf, Wellington New Zealand <u>http://caltex.co.nz</u>			
Transport Emergency Response		New Zealand:	0800-733-835	
Health Emergency	,	Poisons Centre:	0800-764-766 (24 hrs)	
Product Information	on	Email: Product Information: SDS Requests:	lubricants@z.co.nz 0800-733-835 0800-733-835	

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of EPA New Zealand GHS 7.

EPA Group Standard: HSR002606 - Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2020



Signal Word Warning

H361

Hazard Classification

Toxic to Reproduction - Category 2

Hazard Statement

Suspected of damaging fertility or the unborn child.

Prevention Precautionary Statements

- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P281 Use personal protective equipment as required.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.P308+P313 IF exposed or concerned: Get medical advice/attention.

Storage Precautionary Statement

P405 Store locked up.

Product Name: Delo Starplex Moly 3% EP 2

Disposal Precautionary Statement

P501

Dispose of contents/container in accordance with local, regional, national and international regulations.

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION		
CHEMICAL ENTITY	CAS NO	PROPORTION
Highly-refined lubricating base oil Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene Ingredients determined to be Non-Hazardous	- 68411-46-1 -	>60 % 0.1 - 0.5 % Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear selfcontained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Oil mist, mineral		5		10	om

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

ppm Parts of vapour or gas per million of air by volume.

mg/m3 Milligrams of substance per cubic metre of air.

Product Name: Delo Starplex Moly 3% EP 2

om Sampled by a method that does not collect vapour.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Grease
Colour:	Grey
Odour:	Petroleum

Solubility:	Soluble in hydrocarbons; insoluble in water
Specific Gravity:	NAv
Relative Vapour Density (air=1):	>1
Vapour Pressure:	N Av
Flash Point (°C):	200
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	N Av
pH:	N App
Viscosity:	N Av
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: May be an eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 5.0 \text{ mg/L}$ for dust.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg bw}$

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg bw}$

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as a Category 2 - Substances that are suspected human reproductive or developmental toxicants.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Chronic aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Nonrapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) Basel Convention (Hazardous Waste)

This material is subject to the following international agreements:

International Convention for the Prevention of Pollution from Ships (MARPOL)

Product Name: Delo Starplex Moly 3% EP 2

• Annex I - Oil

This material/constituent(s) is covered by the following requirements:

NZ EPA Status: All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

EPA Group Standard: HSR002606 - Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: Revised

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. PLEASE NOTE that although every care has been taken in compiling the above information, it is solely reliant upon data available to us at the date hereof. We believe the data to be correct, however for the reason just stated we are not in a position to warrant its accuracy. With that in mind and given that the full range of possibilities and conditions under which the information may be applied simply cannot be anticipated, YOU ARE CAUTIONED to make your own determinations as to the veracity and the suitability of the information to the particular circumstances that apply, or may apply, to you from time to time. Consistent with that approach it is recommended that where you have a particular purpose which would necessitate a reliance on information of the nature herein you obtain your own independent expert advice particularly structured to the relevant purpose. If this material is printed, circulated, distributed or copied in any manner, it is not to be modified without prior written permission, and further, it is to include the wording of the above disclaimer.

This SDS has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.