



Havoline® Super 2T

Low Smoke, Semi-Synthetic, Low-Stroke Motorcycle Oil

Product Data Sheet

Customer benefits

Powerful throttle response

Power and good acceleration are maintained by providing excellent cleanliness of pistons and exhaust ports, through the reduction of ash and carbon deposits.

Reduces exhaust smoke

Superior combustion characteristics reduce smoke in exhaust emissions, which also provides improved working environment for operators of portable power equipment.

Extends engine life

Semi-synthetic base fluid provides superior lubricity to reduce wear of pistons and cylinders.

Maximizes spark plug life

Low ash additive system reduces ash build-up on spark plugs under all operating conditions.

Applications

- Air and liquid-cooled two-stroke motorcycle engines
- Particularly suitable for Japanese high performance motorcycle engines
- Japanese two-stroke engines fitted to portable power equipment (other than chainsaws)
- Oil-injected engines (except marine outboard) where no fuel/oil premixing is required
- Air-cooled, oil-gasoline premix engines at manufacturers' recommended gasoline-to-oil ratios, up to 50:1
- Two-stroke motorcycle and motor tricycle engines fitted with exhaust catalysts

Not recommended for use in marine outboard engines, in chainsaw or in CNG- or LPG-fuelled engines.

Product features:

- **Havoline® Super 2T** is a premium two-stroke motorcycle oil, that protects vital engine parts while you ride.
- **Havoline® Super 2T** is formulated with a special low ash additive system and designed for engines requiring JASO FC or ISO EGC performance lubricants, including high output machines operating in severe service.



Typical key properties

HAVOLINE® SUPER 2T	
SAE Grade (J1536)	F/M 2
Product Code	500676
Flash Point, PMCC, °C	93
Pour Point, °C	-38
Sulfated Ash, m %	0.13
Viscosity,	
mm ² /s @ 40°C	59.2
mm ² /s @ 100°C	9.4

1905

Performance standards

- JASO FC
JASO Identification Numbers: 065CVX686, 065CVX687
- ISO EGC
- API TC

Service Considerations

Havoline Super 2T is not recommended for use in marine outboard engines, chainsaw engines or any CNG- or LPG-fuelled two-stroke engines.

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.havoline.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific