



# Ultra-Duty® Grease

## Automotive Chassis & Bushing Grease

Product Data Sheet

### Customer benefits

#### Protects metal surfaces

Outstanding film strength and effective EP additive protect against component wear under severe conditions and shock loading. Extreme tackiness maintains sealing collar of grease around bushings which prevents the ingress of abrasive dirt. Excellent resistance to water wash out ensures lubrication is maintained under extremely wet and muddy conditions.

#### Superior adhesiveness

Superior adhesiveness ensures grease stays in place and resists leakage, even in the most severe and shock load conditions, making it possible to extend relubrication intervals.

#### Protects against corrosion

Highly effective rust and corrosion inhibitors protect metal surfaces, even under extremely wet conditions.

### Applications

Can include:

- Heavy-duty transport
- Chassis lubrication
- Construction equipment
- Agricultural tractors
- Off-highway construction
- Mining
- Logging and forestry
- Quarrying

For wheel bearing lubrication of on-highway vehicles, other products that are specifically designed for this application, such as Caltex Starplex EP, are generally preferred.

Usable temperature range in continuous service is:

NLGI 1: -20 to 140°C

NLGI 2: -10 to 140°C

Maximum temperature for short term exposure is 155°C for NLGI 1 grade and 165°C for NLGI 2.

### Product features:

- **Ultra-Duty® Grease** is a premium, heavy-duty EP grease containing a high viscosity mineral oil, lithium thickener, effective EP additive, rust and oxidation inhibitors and tackiness agent.

- **Ultra-Duty® Grease** has stay-in-place properties that make it particularly suitable for automotive equipment operating in wet, muddy or dusty conditions.

Red in color.

## Product specifications

ULTRA-DUTY®GREASE		
KEY PROPERTIES		
	1	2
NLGI Grade	1	2
Product Code	540951	540952
Dropping Point, °C	174	180
Oil Viscosity,		
mm <sup>2</sup> /s @ 40°C	334	380
mm <sup>2</sup> /s @ 100°C	21.0	29.1
Penetration, Worked @ 25°C	325	280
Thickener (Lithium), m %	6	9
Timken OK Load, kg	32	32

1105

## Service considerations

Because of the heavy base oil viscosity and outstanding adhesive properties of Ultra-Duty Grease, it is recommended that a heavy follower plate be used in air-driven grease pumps. Depending on pipe sizing and distance, pumping rates will be lower than for conventional greases of the same NLGI grade. It may be necessary to use Ultra-Duty Grease 1 where pumpability is a primary requirement.

## ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: [www.chevronlubricants.com](http://www.chevronlubricants.com)

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:  
**Chevron Lubricants**  
 – Asia Pacific