



CALTEX

Veritas 800 Marine

Alkaline, Low Speed Diesel Engine System Oil

Product Data Sheet

Customer benefits

Extends time between overhauls

Special detergent and ashless dispersant additive system ensures crankcases and lubricating oil lines are kept free of deposits. The combination of detergency and excellent oxidation stability provides clean piston cooling galleries and chambers.

Protects bearings from corrosive wear

Level of alkalinity reserve ensures that acidic combustion products (which enter the crankcase due to leaks in the connecting rod seals) are effectively neutralized to protect bearings and bright metals against corrosive wear.

Easy oil purification

Combination of highly refined basestocks and special detergent additive system provides excellent water tolerance and separation properties which enable efficient purifier operation. Therefore, water washing is neither necessary nor recommended.

Applications

Crankcase lubrication of:

- Large, low speed (less than 250 rpm), two-cycle crosshead diesel engines
- Particularly suitable for engines with oil-cooled pistons
- Older-type marine trunk piston engines with separate cylinder lubrication
- Marine and stationary applications

Product features:

- **Veritas 800 Marine** is a premium quality, alkaline diesel engine oil designed for crankcase (system) lubrication of large, low speed diesel engines in marine and stationary applications.



Product specifications

| VERITAS 800 MARINE | |
|---|--------|
| KEY PROPERTIES | |
| SAE Grade | 30 |
| Product Code | 560041 |
| Base No., D2896, mg KOH/g | 5.4 |
| Pour Point, °C | -9 |
| FZG Fail Load Stage | 11 |
| Sulfated Ash, m % | 0.7 |
| Viscosity, mm ² /s @ 40°C | 108 |
| mm ² /s @ 100°C | 11.9 |
| Viscosity Index | 98 |
| Zinc, mg/kg | 280 |

1303

Service considerations

Marine system oils are designed for use with active purification systems. As such systems continuously remove contaminants from the oil, long service lives are possible and it is not usual to change out the lubricant on a fixed schedule. Accordingly, it is important that the oil's condition be monitored and the change-out period be determined by means of regular oil analysis and interpretation in accordance with manufacturers' guidelines.

While Veritas 800 Marine has excellent water separation properties, water washing is neither necessary nor recommended. However, contamination with other engine oils may drastically affect its ability to maintain these excellent water separation characteristics.

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal.

To obtain a MSDS for this product, visit:
www.chevronlubricants.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific