



Customer benefits

Protect metal surfaces

The use of special antiwear additives gives increased working life of the chain, bar and sprocket.

Less waste

The tacky quality of the product minimises sling-off from the chain.

Effective performance

Keeps the saw clean by flushing away wood chips, gum and dust and by removing pitch and preventing further pitch build-up on the chain and bar. Minimises chain adjustment and chain replacement.

Applications

Can include:

- Chain, bar and sprocket on all types of chainsaws, using either hand operated or automatic oilers.
- Chain driven machinery, including lumber carriers and farm equipment.

Product features:

- **Chain & Bar Oil** is a tough, tacky lubricant designed for lubrication of the chain, bar and sprocket on all types of chainsaws and chain driven machinery. It is made from highly refined high viscosity index base oils along with a highly effective tackiness agent to resist throw-off.



Product specifications

CHAIN & BAR OIL KEY PROPERTIES	
Product Code	541600
Flash Point, °C	250
Oil Viscosity, mm ² /s@ 40°C	150
Density at 15 °C kg/L	0.889

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.chevronlubricants.com.

1106

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific