



Two Stroke Lawn Mower Oil

Two-Stroke Motor Oil

Product Data Sheet

Customer benefits

Engine protection

Good lubricity characteristics help protect against friction, wear and scuffing damage.

Long spark plug life

Low ash additive system helps reduce spark plug fouling, allowing long spark plug life.

Applications

- Two-stroke lawn mower engines
- Two-stroke lawn and garden tools, including weedeaters, trimmers, edgers, blowers
- Portable two-stroke generators
- Oil-injected engines in land-based service where no fuel/oil premixing is required
- Air-cooled, oil-gasoline premix engines at manufacturers' recommended gasoline-to-oil ratios, up to 50:1

Not suitable for use in marine two-stroke outboard engines.

Not recommended for use for use in two-stroke chainsaw engines.

Product features:

- **Two Stroke Lawn Mower Oil** is an all-mineral two-stroke motor oil formulated with a low ash additive system.
- **Two Stroke Lawn Mower Oil** is prediluted with a low volatility, low odor solvent to facilitate mixing with gasoline at all temperatures.
- **Two Stroke Lawn Mower Oil** is designed for engines requiring JASO FB or ISO EGB performance lubricants.



Product specifications

TWO STROKE LAWN MOWER OIL KEY PROPERTIES	
SAE Grade	F/M 2
Product Code	501600
Flash Point PMCC, °C	124
Pour Point, °C	-19
Sulfated Ash, mass %	0.06
Viscosity,	
mm ² /s @ 40°C	67.7
mm ² /s @ 100°C	9.05

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.caltex.com.

1301

Performance standards

- JASO FB
- ISO EGB

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific



Service Considerations

Two Stroke Lawn Mower Oil is intended for use in smaller two-stroke engines as used in lawn and garden tools that habitually operate at relatively low load factors.

It is not suitable for and should not be used any two-stroke marine outboard engines. For these a purpose-designed high performance ashless two-stroke engine oil, such as Caltex Super Outboard 3, should be used.

Two Stroke Lawn Mower Oil is not recommended for use in chainsaw engines, for which a properly formulated two-stroke chainsaw engine oil should be used.

It is not intended for use in any CNG- or LPG-fuelled two-stroke engines, or any two-stroke engines equipped with exhaust catalyst systems.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific